Having trouble viewing this email? Click here



For More Information Contact: Bill Mosher at <u>billm@forespar.com</u> or (414) 688-9979 <u>Link to T-150 Product Web Page</u>

NEW PRODUCT RELEASE

December 3, 2013

Marelon® T-150 Raw Water Strainer Offers Flexible Installation

Unique Mounting Bracket Allows Compact Strainer To Be Positioned As Needed In Tight Locations





Rancho Santa Margarita, CA - Forespar's new Marelon T-150 Strainer provides a compact installation alternative for raw water filtration without

1 of 2 6/27/2014 9:07 AM

compromising filtration rates. It features a T-Head body design and unique mounting bracket that allows the T-150 to be installed in tight or hard-to-reach locations where traditional raw water strainers will not fit. Despite its smaller size, it offers all the benefits of traditional "top basket" strainers.

Carefully engineered and tested, the T-150 has the same durability, water flow and pressure requirements of Forespar's popular MF-810 strainer in a smaller package. The included mounting bracket only requires two 1/4" fasteners to firmly attach it to a bulkhead or stringer, and its unique C clamp shape allows the strainer to be snapped into place and rotated as needed to face any direction. The strainer body and mounting bracket are constructed using Forespar's tough ABYC compliant Marelon composite plastic and a clear polycarbonate screw-on filter bucket offers easy viewing of the stainless steel filter basket without removal.

Extensively vacuum and vibration tested, it also uses a replaceable bucket gasket for a firm and positive seal every time. The T-150 fits 1-1/2" Female NPSM (Parallel Threads) Ports to which you can attach a straight or 90° Hose Barb Tailpipe as needed. Adaptors are also available for 3/4", 1", 1-1/8" & 1-1/4" fittings.

T-150 Specifications:

- 5-1/4" Wide (at the "t") x 8-1/4" tall x 4" diameter
- 1-1/2" Female npsm ports
- 40 GPM +
- Mesh Size: #8
- Vacuum Tested to -25 in Hg
- Vibration test of 50,000+ cycles at 1400 cycles per minute
- Pressure Tested to 150 psi @ 700 mac, or F--100 psi @ 1250 F (Not designed for pressure spikes exceeding max psi)

Part# 906166 / MSRP \$149.50 ea.

####

Forward email





This email was sent to sforesman@forespar.com by <u>dealernews@forespar.com</u> | <u>Update Profile/Email Address</u> | Instant removal with <u>SafeUnsubscribe</u>[™] | <u>Privacy Policy</u>.

| 22322 Gilberto | Rancho Santa Margarita | California | 92688

2 of 2 6/27/2014 9:07 AM