



**Combination Bow & Foredeck Light  
ML-2 P/N 132000**



**INSTALLATION INSTRUCTIONS**

This 20 point navigation (Running) light has been carefully engineered and manufactured to meet the current international requirements for marine navigation lights (72 COL-REGS-Annex 1, USCG Nav. Rule CG-169) for boats under 20 meters in length. For proper function the light must be precisely mounted on the center line of the forward surface of the mast no less than 1 meter above any other navigational light which is to be operated at the same time as this 20 point light.

**BULB REPLACEMENT**

To replace the running light bulb, carefully twist the lens counterclockwise and lift off. If the O-ring seal does not come off with the lens, carefully remove it from its recess and slip it into the lens base. Replace the bulb with a WN211 festoon type obtainable from your dealer. Part No. 132025

To replace the 20 watt quartz halogen bulb, remove the lower cap, twist counterclockwise to remove. Be sure to feel the "click" lock when you replace the lower cap. Draw the bulb/reflector assembly downward and disconnect it from the slide on connector. Replace with Forespar® bulb/reflector assembly from your dealer. Part No. 132035

**FORESPAR PRODUCTS CORP.**  
22322 Gilberto Rancho Santa Margarita, CA  
Ph. (949) 858-8820 Fax (949) 858-0505